



Scharlau S.L.

Gato Pérez, 33. Pol. Ind. Mas d'en Cisa
08181 Sentmenat
+34937456400
scharlab@scharlab.com

CERTIFICATE OF ANALYSIS

Product: AC0781	Hydrochloric acid, 35%, Ultratrace®, ppt-trace analysis grade	Batch	
		Quality release date	30/4/2020
		Expiry date	4/2023
Analysis		Batch value	Specifications
assay (acidimetric)	33%	32 - 35%	
aluminium (Al)	< 2 ppt	max. 20 ppt	
antimony (Sb)	< 0,1 ppt	max. 20 ppt	
arsenic (As)	< 1 ppt	max. 50 ppt	
barium (Ba)	< 0,2 ppt	max. 10 ppt	
beryllium (Be)	< 0,01 ppt	max. 10 ppt	
bismuth (Bi)	< 0,01 ppt	max. 10 ppt	
boron (B)	< 5 ppt	max. 100 ppt	
cadmium (Cd)	< 0,02 ppt	max. 10 ppt	
calcium (Ca)	< 10 ppt	max. 10 ppt	
cerium (Ce)	< 0,01 ppt	max. 10 ppt	
cesium (Cs)	< 0,01 ppt	max. 10 ppt	
chromium (Cr)	< 0,5 ppt	max. 10 ppt	
cobalt (Co)	< 0,05 ppt	max. 10 ppt	
copper (Cu)	< 0,2 ppt	max. 10 ppt	
dysprosium (Dy)	< 0,01 ppt	max. 1 ppt	
erbium (Er)	< 0,01 ppt	max. 1 ppt	
europtium (Eu)	< 0,01 ppt	max. 1 ppt	
gadolinium (Gd)	< 0,01 ppt	max. 1 ppt	
gallium (Ga)	< 0,01 ppt	max. 10 ppt	
gold (Au)	< 1 ppt	max. 50 ppt	
hafnium (Hf)	< 0,01 ppt	max. 10 ppt	
holmium (Ho)	< 0,01 ppt	max. 1 ppt	
indium (In)	< 0,01 ppt	max. 1 ppt	
iron (Fe)	< 5 ppt	max. 10 ppt	
lanthanum (La)	< 0,01 ppt	max. 1 ppt	
lead (Pb)	< 0,02 ppt	max. 10 ppt	
lithium (Li)	< 0,05 ppt	max. 10 ppt	
lutetium (Lu)	< 0,01 ppt	max. 10 ppt	
magnesium (Mg)	< 0,5 ppt	max. 10 ppt	
manganese (Mn)	< 0,02 ppt	max. 10 ppt	
mercury (Hg)	< 20 ppt	max. 50 ppt	
molybdenum (Mo)	< 1 ppt	max. 10 ppt	
neodymium (Nd)	< 0,01 ppt	max. 1 ppt	
nickel (Ni)	< 5 ppt	max. 20 ppt	
niobium (Nb)	< 0,01 ppt	max. 1 ppt	
palladium (Pd)	< 0,1 ppt	information only	

This certificate does not release the user from their control upon receipt of the goods.

You can get a copy of any of our COA from our web site: www.scharlab.com

M. Canet
Laboratory Manager

Scharlab S.L. - Certificate of Analysis

Product: AC0781	Hydrochloric acid, 35%, Ultratrace®, ppt-trace analysis grade	Batch Quality release date Expiry date	30/4/2020 4/2023
Analysis		Batch value	Specifications
platinum (Pt)		< 1 ppt	information only
potassium (K)		< 1 ppt	max. 10 ppt
praseodymium (Pr)		< 0,01 ppt	max. 1 ppt
rhenium (Re)		< 0,01 ppt	max. 10 ppt
rhodium (Rh)		< 0,01 ppt	max. 10 ppt
rubidium (Rb)		< 0,01 ppt	max. 10 ppt
ruthenium (Ru)		< 0,01 ppt	max. 10 ppt
samarium (Sm)		< 0,01 ppt	max. 1 ppt
scandium (Sc)		< 0,05 ppt	max. 10 ppt
selenium (Se)		< 20 ppt	information only
silver (Ag)		< 0,05 ppt	max. 10 ppt
sodium (Na)		< 1 ppt	max. 10 ppt
strontium (Sr)		< 0,02 ppt	max. 10 ppt
tantalum (Ta)		< 0,01 ppt	information only
tellurium (Te)		< 0,02 ppt	max. 1 ppt
terbium (Tb)		< 0,01 ppt	max. 1 ppt
thallium (Tl)		< 0,01 ppt	max. 10 ppt
thorium (Th)		< 0,01 ppt	max. 1 ppt
thulium (Tm)		< 0,01 ppt	max. 1 ppt
tin (Sn)		< 0,5 ppt	max. 20 ppt
titanium (Ti)		< 0,1 ppt	max. 10 ppt
tungsten (W)		< 0,1 ppt	max. 10 ppt
uranium (U)		< 0,01 ppt	max. 1 ppt
vanadium (V)		< 0,1 ppt	max. 10 ppt
ytterbium (Yb)		< 0,01 ppt	max. 1 ppt
yttrium (Y)		< 0,01 ppt	max. 1 ppt
zinc (Zn)		< 0,5 ppt	max. 10 ppt
zirconium (Zr)		< 0,01 ppt	max. 10 ppt

Preparation

Operations are conducted under Class 100 or better clean-room conditions.

The product is bottled in specially cleaned fluoropolymer bottles to remove leachable metals.

Measurement

Most elements are determined by ICP-MS using sample preconcentration. The results are the average of three aliquots subsampled from three samples representative of the batch. The samples are slowly evaporated to dryness.

For volatile elements, the samples are diluted then directly injected into ICP-MS.

Values are below 3 times the standard deviation of the blank, otherwise stated.

Storage and use

For ppt-trace analysis

If the product is stored at room temperature and avoiding exposure to light and unopened, this solution is stable for 3 years from the date of manufacturing.

Once the bottle is opened, keep tightly closed at room temperature. Avoid exposure to light and to contaminants. The inner pack of plastic bag and bottle should be opened under Class 100 particle conditions.

The use of plastic gloves, hair net and a clean room suit is also advised.

In order to maintain trace metal purity if you made solutions from this product, these solutions must be made in a trace metal clean room and the water must be of the same trace metal quality or better.

This certificate does not release the user from their control upon receipt of the goods.

You can get a copy of any of our COA from our web site: www.scharlab.com

M. Canet
Laboratory Manager