

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

• **Trade name:** Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

• **Article number:** AC0141

• **CAS Number:**

141-78-6

• **EC number:**

205-500-4

• **Index number:**

607-022-00-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

• **Application of the substance / the preparation:** Laboratory reagent

1.3 Details of the supplier of the safety data sheet

• **Manufacturer/Supplier:**

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa

08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com

Internet Web Site: www.scharlab.com

• **Regional representation:**

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa

08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com

Internet Web Site: www.scharlab.com

• **Further information obtainable from:** Technical Department

1.4 Emergency telephone number:

Please contact the regional Scharlab distributor/dealer in your country

During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

• **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



corrosion

Skin Corr. 1 H314 Causes severe skin burns and eye damage.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 1)

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The substance is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS05 GHS07

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.1 Substances**
- **CAS No. Description**
141-78-6 ethyl acetate
- **Identification number(s)**
- **EC number:** 205-500-4
- **Index number:** 607-022-00-5

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
Seek medical treatment.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 2)

• **After skin contact:**

Generally the product does not irritate the skin.
Immediately wash with water and soap and rinse thoroughly.
Immediately remove all contaminated clothing.
Wash contaminated clothing before reuse.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
If the casualty wears contact lenses, they should be removed as long as they are not stuck to the eyes, otherwise additional damage may occur.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting, danger of perforation.
Never give anything by mouth to an unconscious person.
If the affected person vomits, keep the head down so that the vomit does not enter the lungs.

• **4.2 Most important symptoms and effects, both acute and delayed**

The main symptoms are described for the different cases of contact: skin, eyes, inhalation and ingestion.

• **4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

SECTION 5: Firefighting measures

• **5.1 Extinguishing media**

• **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

• **For safety reasons unsuitable extinguishing agents:**

Water with full jet

Water

• **5.2 Special hazards arising from the substance or mixture**

Vapours may create explosive mixtures with air.
Vapours are heavier than air and spread along the ground.
Prevent any contact with combustible substances.
Do not breathe fire or explosion gases.
In case of incomplete combustion, carbon monoxide (CO) may be formed.

• **5.3 Advice for firefighters**

• **Protective equipment:**

Respiratory protection and full chemical protective clothing must be provided for extinguishing work.
Cool exposed containers by water spray or water mist.

• **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

• **6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.
Eliminate all sources of ignition.
Avoid contact with skin, eyes and clothing.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.

• **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

• **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 3)

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Do not eat, drink or smoke during use.
Wash hands after handling.

Information about fire - and explosion protection:

Use explosion-proof apparatus / fittings and spark-proof tools.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool, dry and well-ventilated place.
Store only in unopened original receptacles.
Suitable material for receptacles and pipes: steel or stainless steel.
Store in a cool location.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:**

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
See product's label for recommended storage temperature.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****141-78-6 ethyl acetate**WEL Short-term value: 1468 mg/m³, 400 ppmLong-term value: 734 mg/m³, 200 ppm**DNELs**

DNEL consumer, prolonged. Systematic effects:

- Inhalative: 367 mg/m³
- Dermic: 37 mg/kg body weight
- Oral: 4.5 mg/kg body weight

DNEL consumer, acute. Local effects: Inhalative - 734 mg/m³DNEL consumer, acute. Systematic effects: Inhalative - 734 mg/m³

DNEL for workers, cronic. Systematic effects:

- Inhalative: 734 mg/m³
- Dermic: 63 mg/kg body weight

DNEL worker, cronic. Acute local and systematic effects: Inhalative - 1468 mg/m³**PNECs**

PNEC (Fresh water): 0.24 mg/L

PNEC (Sea water): 0.024 mg/L

PNEC (Intermittent Release): 1.65 mg/l

PNEC (Freshwater sediments): 1.15 mg/kg

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 4)

PNEC (Seawater sediments): 0.115 mg/kg

PNEC (Soil): 0.148 mg/kg

PNEC (Residual water depuration system): 650 mg/l

• **Additional information:** The lists valid during the making were used as basis.

• 8.2 Exposure controls

• **Appropriate engineering controls** No further data; see item 7.

• **Individual protection measures, such as personal protective equipment**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• **Respiratory protection:** Not required.

• **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

• **General Information**

• **Physical state**

Fluid

• **Colour:**

Colourless

• **Odour:**

Fruit-like

• **Odour threshold:**

Not determined.

• **Melting point/freezing point:**

-83 °C

• **Boiling point or initial boiling point and boiling range**

77-78 °C

• **Flammability**

Highly flammable.

• **Lower and upper explosion limit**

• **Lower:**

2.1 Vol %

• **Upper:**

11.5 Vol %

• **Flash point:**

-4 °C

• **Ignition temperature:**

460 °C

• **Decomposition temperature:**

Not determined.

• **pH**

11-12

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 5)

- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Dynamic at 20 °C:** 0.44 mPas
- **Solubility**
- **water at 20 °C:** 79 g/l
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 100 hPa
- **Density and/or relative density**
- **Density at 20 °C:** 0.902 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Auto-ignition temperature:** Not determined.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Molecular weight** 88 g/mol
- **Change in condition**
- **Evaporation rate** Not determined.
- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Highly flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Can be distilled without decomposing at normal pressure.
- **10.3 Possibility of hazardous reactions** Violent reactions with strong alkalis and oxidising agents.
- **10.4 Conditions to avoid** Heat, flame and sparks

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 6)

• **10.5 Incompatible materials:**

Strong acids
Strong bases
Strong oxidising agents.

• **10.6 Hazardous decomposition products:**

No dangerous decomposition products known.
Ethanoic acid
In case of fire, formation of carbon monoxide CO and carbon dioxide CO₂.

SECTION 11: Toxicological information

• **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

• **Acute toxicity**

• **LD/LC50 values relevant for classification:**

Oral LD50 5,620 mg/kg (rabbit)
Dermal LD50 >18,000 mg/kg (rabbit)
Inhalative LC50/4 h 56 mg/l (rat)

• **Skin corrosion/irritation** Causes severe skin burns and eye damage.

• **Serious eye damage/irritation** Causes serious eye irritation.

• **STOT-single exposure** May cause drowsiness or dizziness.

• **11.2 Information on other hazards**

• **Endocrine disrupting properties** Substance is not listed.

SECTION 12: Ecological information

• **12.1 Toxicity**

• **Aquatic toxicity:**

Toxicity to fish

LC50 - Pimephales promelas (Fathead piscardo) - 230 mg/L - 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (large sea flea) - 610 mg/L - 48 h

NOEC - Daphnia magna (large sea flea) - 21 mg/L - 2.4h

Toxicity to algae

EC50 - Scenedesmus subspicatus - 5600 mg/l - 48 h

• **12.2 Persistence and degradability**

Rapid photochemical oxidation in air.

Fully biodegradable.

• **12.3 Bioaccumulative potential**

Due to the distribution coefficient n-octanol/water an accumulation in organisms is possible.

• **12.4 Mobility in soil** No further relevant information available.

• **12.5 Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

• **12.7 Other adverse effects**

• **Additional ecological information:**

• **General notes:**

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

only low water-dangerous.

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

When mixed with other products, other disposal routes may be necessary.

In case of doubt, seek advice from the supplier of the product or the local authorities.

Must be specially treated adhering to official regulations.

Separate the polluting water by means of a separating funnel and dispose of it in accordance with the directives of the competent official bodies.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1173

14.2 UN proper shipping name

ADR

IMDG, IATA

1173 ETHYL ACETATE

ETHYL ACETATE

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

33

EMS Number:

F-E,S-D

Stowage Category

B

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

1L

Transport category

2

Tunnel restriction code

D/E

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves· **UN "Model Regulation":**

UN 1173 ETHYL ACETATE, 3, II

(Contd. of page 8)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I -**
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product Safety Department· **Contact:** msds@scharlab.com· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 9)

Annex: Exposure scenario 1

- **1 - Short title of the exposure scenario** Industrial use
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Process category** PROC15 Use as laboratory reagent
- **Environmental release category**
ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **2 - Conditions of use**
- **Duration and frequency**
Days of issuance (days/year): 300
5 workdays/week.
- **Worker** Permanent use with exposure up to 8 hrs every work day of the week.
- **Environment**
Wastewater must be treated by a municipal STP. Municipal STP discharge rate <2E3 m³/d.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity**
5000 tons per year
17 kg per day
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure**
Fraction released to the air by the process (initial release prior to MGR): 1
Fraction released into the wastewater by the process (initial release prior to MGR): 1
Fraction released to the soil by the process (initial release prior to MGR): 0.2
- **Other operational conditions affecting worker exposure**
Use is assumed at a temperature not more than 20°C above ambient temperature.
Avoid contact with eyes.
Take precautionary measures against static discharge.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
Keep good industrial hygiene.
Dike storage facilities to prevent soil and water contamination in case of spillage.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Tightly sealed goggles
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Soil** No special measures required.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 10)

• Disposal measures

Estimate of the amount that has gone to waste treatment, not greater than: 5 %
Forward for special waste incineration in compliance with local legal provisions.
Disposal must be made according to official regulations.
Ensure that waste is collected and contained.
External recovery of waste. Appropriate treatment type: redistillation.

• 3 - Exposure estimation**• Worker (dermal)** PROC 15: 0.34 (mg/kg/d)**• Worker (inhalation)** PROC 15: 30 (mg/m³)**• Environment**

The highest environmental exposure to be expected in purification plants is 0.822 mg / L.

The highest environmental exposure to be expected for surface waters is 0.0851 mg / L.

The maximum exposure to expect on freshwater (sediment) 0.113 mg/L. RCR: 0.403

Maximum concentration/emission: Seawater 0.0085 mg/l

The maximum exposure to expect on marine water (sediment) 0.0013 mg/L. RCR: 0.0403

The maximum exposure to expect on agricultural soil 0.0002 mg/L. RCR: 0.0007

• 4 - Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

Inhalation (vapour). From an exposure of 1 to 4 hours to an exposure of more than 4 hours, multiply by 1.7.

For the risk assessment, the tools recommended by ECHA can be used.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 11)

Annex: Exposure scenario 2

- **1 - Short title of the exposure scenario** Laboratory use
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Process category** PROC15 Use as laboratory reagent
- **Environmental release category**
ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **2 - Conditions of use**
- **Duration and frequency**
Days of issuance (days/year): 300
5 workdays/week.
- **Worker** Permanent use with exposure up to 8 hrs every work day of the week.
- **Environment**
Wastewater must be treated by a municipal STP. Municipal STP discharge rate <2E3 m³/d.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity**
5000 tons per year
17 kg per day
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure**
Fraction released to the air by the process (initial release prior to MGR): 1
Fraction released into the wastewater by the process (initial release prior to MGR): 1
Fraction released to the soil by the process (initial release prior to MGR): 0.2
- **Other operational conditions affecting worker exposure**
Use is assumed at a temperature not more than 20°C above ambient temperature.
Avoid contact with eyes.
Take precautionary measures against static discharge.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
Keep good industrial hygiene.
Dike storage facilities to prevent soil and water contamination in case of spillage.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Tightly sealed goggles
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 12.04.2023

Version number 9.0 (replaces version 8.0)

Revision: 12.04.2023

Trade name: Ethyl acetate, 99,8%, anhydrous (max. 0,005% H₂O), with molecular sieves

(Contd. of page 12)

- **Soil** No special measures required.

- **Disposal measures**

Estimate of the amount that has gone to waste treatment, not greater than: 5 %

Forward for special waste incineration in compliance with local legal provisions.

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

External recovery of waste. Appropriate treatment type: redistillation.

- **3 - Exposure estimation**

- **Worker (dermal)** PROC 15: 0.34 (mg/kg/d)

- **Worker (inhalation)** PROC 15: 30 (mg/m³)

- **Environment**

The highest environmental exposure to be expected in purification plants is 0.822 mg / L.

The highest environmental exposure to be expected for surface waters is 0.0851 mg / L.

The maximum exposure to expect on freshwater (sediment) 0.113 mg/L. RCR: 0.403

Maximum concentration/emission: Seawater 0.0085 mg/l

The maximum exposure to expect on marine water (sediment) 0.0013 mg/L. RCR: 0.0403

The maximum exposure to expect on agricultural soil 0.0002 mg/L. RCR: 0.0007

- **4 - Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

Inhalation (vapour). From an exposure of 1 to 4 hours to an exposure of more than 4 hours, multiply by 1.7.

For the risk assessment, the tools recommended by ECHA can be used.