

Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

· Article number: AL0312

• **CAS Number:** 67-63-0

• **EC number:** 200-661-7

• *Index number:* 603-117-00-0

Registration number 01-2119457558-25-XXXX

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

· Process category

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC15 Use as laboratory reagent

- · Application of the substance / the preparation: Laboratory reagent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com Internet Web Site: www.scharlab.com

· Regional representation:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com Internet Web Site: www.scharlab.com

- · Further information obtainable from: technical department
- 1.4 Emergency telephone number:

Please contact the regional Scharlab distributor/dealer in your country During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.*vPvB:* Not applicable.

SECTION 3: Composition/information on ingredients

3.1 Chemical characterisation: Substances

· CAS No. Description 67-63-0 propan-2-ol

Identification number(s)

EC number: 200-661-7

· Index number: 603-117-00-0

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Seek medical treatment.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Position and transport stably in side position.

· After inhalation:

Take affected persons into fresh air and keep quiet.

Separate casualty from the danger zone. Place the affected in the most comfortable position and protéjasele cold.

In severe cases such as cardiorespiratory arrest, artificial respiration techniques such as mouth-to-mouth resuscitation, cardiac massage, oxygen supply, etc. will be applied.

(Contd. on page 3)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 2)

Seek immediate medical advice.

· After skin contact:

Generally the product does not irritate the skin.

Immediately remove contaminated clothing.

Immediately wash with water and soap and rinse thoroughly.

Wash contaminated clothing before reuse.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. In the event that the injured person wears contact lenses, they must be removed as long as they are not stuck to the eyes, otherwise additional damage could occur.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting. Risk of perforation.

Never give anything by mouth to an unconscious person.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Pressurized water jet
- · 5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

Fire may cause evolution of:

Carbon dioxide (CO2)

Carbon monoxide (CO)

Nitrogen oxides

- · 5.3 Advice for firefighters
- Protective equipment:

Cool exposed containers with water spray or mist.

In the work of extinction it is necessary to provide respiratory protection and full chemical protective clothing.

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Isolate leaks as long as it does not pose an additional risk to the people who perform this function. Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 3)

· 6.3 Methods and material for containment and cleaning up:

Dilute with plenty water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Wear an individual protective equipment.

Wear chemically sealed goggles and / or face shield.

Avoid contact with eyes and skin.

Avoid breathing mist/vapours/spray.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not eat, drink or smoke during use.

Wash hands after any manipulation.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Vapors are heavier than air and may spread along floors.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage.
- · Requirements to be met by storerooms and receptacles:

Store in a cool, dry, well-ventilated place.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store under lock and key and with access restricted to technical experts or their assistants only.

Avoid sources of heat, radiation, static electricity and contact with food.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

· DNELs

DNEL for workers, cronic. Systematic effects:

- Inhalative: 500 mg/m3

- Dermic: 888 mg/kg body weight

DNEL consumer, prolonged. Systematic effects:

- Inhalative: 89 mg/m3

- Dermic: 319 mg/kg body weight

- Oral: 26 mg/kg body weight

(Contd. on page 5)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 4)

· PNECs

PNEC (Fresh water): 140.9 mg/L PNEC (Sea water): 140.9 mg/L

PNEC (Freshwater sediments): 552 mg/kg PNEC (Seawater sediments): 552 mg/kg

PNEC (Soil): 28 mg/kg

PNEC (Residual water depuration system): 2251 mg/kg

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:

Form:
Colour:
Colour:
Colour:
Alcohol-like
Colour threshold:
22 - 200 ppm
PH-value:
Not determined.

· Change in condition

Melting point/freezing point: -89.5 °C Initial boiling point and boiling range: 82 °C

(Contd. on page 6)



Printing date 19.07.2022 Revision: 19.07.2022 Version number 9.0

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 5)

12 °C · Flash point:

· Flammability (solid, gas): Not applicable.

425 °C · Ignition temperature:

· Decomposition temperature: Not determined. · Auto-ignition temperature: Not determined.

Product is not explosive. However, formation of · Explosive properties:

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 2 Vol % 12 Vol % Upper: Vapour pressure at 20 °C: 43 hPa 0.785 g/cm³ · Density at 20 °C: Not determined. Relative density Vapour density Not determined. Evaporation rate Not determined.

· Solubility in / Miscibility with

water at 20 °C: 1 g/l

 Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic at 20 °C: 2.43 mPas Kinematic: Not determined.

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

- 10.4 Conditions to avoid Heat, open flames and sparks
- 10.5 Incompatible materials:

Oxidising agents.

Acids

Acid anhydrides.

Halogenated compounds.

Aluminium and mild steel.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

Oral LD50 5840 mg/kg (rat)

Dermal LD50 13900 mg/kg (rabbit)

(Contd. on page 7)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 6)

Inhalative LC50/4 h >25000 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

LC50 - Pimephales promelas (Fathead piscardo) - 9640 mg/L - 96 h

EC50 - Daphnia magna (large sea flea) - >10000 mg/L - 24 h

12.2 Persistence and degradability

Biodegradation = >98 %

Easily biodegradable

· 12.3 Bioaccumulative potential

Log Pow: 0.05 (25°C)

Does not accumulate in organisms

- · 12.4 Mobility in soil Very mobile
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must be specially treated adhering to official regulations.

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 8)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 7)

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

· 14.2 UN proper shipping name

· ADR · IMDG, IATA

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA

UN1219

1219 ISOPROPANOL (ISOPROPYL ALCOHOL) ISOPROPANOL (ISOPROPYL ALCOHOL)



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 33
EMS Number: 3-06
Stowage Category B

· Stowage Category · 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

ADR

Limited quantities (LQ)
Transport category
Tunnel restriction code

· UN "Model Regulation": UN 1219 ISOPROPANOL (ISOPROPYL

ALCOHOL), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I -
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II Substance is not listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

(Contd. on page 9)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: product safety department
- · Contact: msds@scharlab.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

(Contd. on page 10)



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 9)

Annex: Exposure scenario 1

- · 1 Short title of the exposure scenario Industrial use
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Process category PROC15 Use as laboratory reagent
- · Environmental release category

ERC2 Formulation into mixture

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Description of the activities / processes covered in the Exposure Scenario
 See section 1 of the annex to the Safety Data Sheet.

- · 2 Conditions of use
- Duration and frequency 8hrs (full working shift).
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting worker exposure

Ensure adequate ventilation, especially in closed rooms.

Assumes use at not more than 20 °C above ambient temperature, unless stated differently.

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure Keep out of the reach of children.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Take care of good cleanliness and tidiness.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

- Environmental protection measures
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · 3 Exposure estimation
- · Worker (oral)

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

The exposure estimation was carried out in accordance with ECETOC TRA.

· Worker (dermal)

The exposure estimation was carried out in accordance with ECETOC TRA.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

(Contd. on page 11)





The wise thoice

he wise thoice

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

The wise choice

The wise thoice

(Contd. of page 10)

- · Consumer Not relevant for this Exposure Scenario.
- 4 Guidance for downstream users No further relevant information available.

(Contd. on page 12)

The wise choice

The wise thoice

The wise choice

The wise choice



Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 11)

Annex: Exposure scenario 2

- · 1 Short title of the exposure scenario Laboratory use
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Process category PROC15 Use as laboratory reagent
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

- Description of the activities / processes covered in the Exposure Scenario
 See section 1 of the annex to the Safety Data Sheet.
- · 2 Conditions of use
- · Duration and frequency 8hrs (full working shift).
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material
- Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting worker exposure

Ensure adequate ventilation, especially in closed rooms.

Assumes use at not more than 20 °C above ambient temperature, unless stated differently.

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure Keep out of the reach of children.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Take care of good cleanliness and tidiness.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

· Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

- · Environmental protection measures
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · 3 Exposure estimation
- · Worker (oral)

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

The exposure estimation was carried out in accordance with ECETOC TRA.

· Worker (dermal)

The exposure estimation was carried out in accordance with ECETOC TRA.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

(Contd. on page 13)





The wise thoice

ine wise thoice

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.07.2022 Version number 9.0 Revision: 19.07.2022

The wise choice

The wise choice

Trade name: 2-Propanol, for analysis, ExpertQ®, ACS, ISO, Reag. Ph Eur

(Contd. of page 12)

The wise choice

The wise thoice

· Consumer Not relevant for this Exposure Scenario.

The wise choice

The wise thoice

· 4 - Guidance for downstream users No further relevant information available.