according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Scharlau

Version number 2.0

Revision: 02.06.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: n-Butylamine, EssentQ®
- · Article number: BU0020
- · CAS Number:
- 109-73-9
- **EC number:** 203-699-2
- Index number: 612-005-00-0
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

wiseche

- Application of the substance / the preparation: Laboratory reagent
- · 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: Scharlab, S.L.
 C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN
 Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65
 email: scharlab@scharlab.com
 Internet Web Site: www.scharlab.com
 Regional representation:

- Scharlab, S.L. C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65 email: scharlab@scharlab.com Internet Web Site: www.scharlab.com
- Further information obtainable from: technical department
- the regional Scharlab distributor/dealer in your country During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS06 skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin. Acute Tox. 3 H331 Toxic if inhaled.

GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Scharlau

Version number 2.0

Revision: 02.06.2021

Trade name: n-Butylamine, EssentQ®

(Contd. of page 1)



SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:
- Immediately remove any clothing soiled by the product.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Scharlau

Version number 2.0

Revision: 02.06.2021

Trade name: n-Butylamine, EssentQ®

(Contd. of page 2) Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:
- Call for a doctor immediately.
- Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust) Use neutralising agent. Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 07.06.2021 Version number 2.0

Revision: 02.06.2021

Trade name: n-Butylamine, EssentQ®

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

Scharlau

- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists valid during the making were used as basis.


· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

wise choic

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Scharlau

Version number 2.0

Revision: 02.06.2021

Trade name: n-Butylamine, EssentQ®

(Contd. of page 4)

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information
 Appearance:
- Form:
 - Colour:
- · Odour:
- Odour threshold:
- · pH-value:

Colourless Amine-like Not determined.

Not determined.

Fluid

- Change in condition Melting point/freezing point: -50 °C Initial boiling point and boiling range: 77.8 °C
- · Flash point:
- Flammability (solid, gas):
- · Ignition temperature:
- · Decomposition temperature:
- · Auto-ignition temperature:
- Explosive properties:
- Explosion limits: Lower: Upper:
- Vapour pressure at 20 °C:
- Density at 20 °C:
- · Bulk density:
- · Relative density
- · Vapour density
- · Evaporation rate
- Solubility in / Miscibility with water at 20 °C:
- Partition coefficient: n-octanol/water:
- Viscosity: Dynamic: Kinematic:
- •9.2 Other information

312 °C Not determined.

-35 °C

Not determined.

Not applicable.

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

1.7 Vol % 10 Vol %

100 hPa

0.739 g/cm³

1 kg/m³ Not determined. Not determined. Not determined.

1 g/l

Not determined.

Not determined. Not determined.

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Scharlau

Version number 2.0

Revision: 02.06.2021

Trade name: n-Butylamine, EssentQ®

(Contd. of page 5) • **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
 Harmful if swallowed.
- Toxic in contact with skin or if inhaled.
- LD/LC50 values relevant for classification:
- Oral LD50 366 mg/kg (rat)
- Dermal LD50 850 mg/kg (rabbit)
- Inhalative LC50/4 h 0.8 mg/l (mouse)
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes severe skin burns and eye damage.
- · Serious eye damage/irritation
- Causes severe skin burns and eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Must not reach sewage water or drainage ditch undiluted or unneutralised.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Scharlau

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Version number 2.0


Revision: 02.06.2021

(Contd. of page 6)

Trade name: n-Butylamine, EssentQ®

· Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.



according to 1907/2006/EC, Article 31

Printing date 07.06.2021

Scharlau

Version number 2.0

Revision: 02.06.2021

hewisecho

(Contd. of page 7)

Trade name: n-Butylamine, EssentQ®

· UN "Model Regulation":

UN 1125 N-BUTYLAMINE, 3 (8), II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I -
- Seveso category
 H2 ACUTE TOXIC
 P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II
 Substance is not listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
- · Department issuing SDS: product safety department
- Contact: msds@scharlab.com
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Acute Tox. 4: Acute toxicity Category 4 Acute Tox. 3: Acute toxicity – Category 3
- Skin Corr. 1A: Skin corrosion/irritation Category 3

re wise choic

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3