Printing date 21.12.2022

Scharlau

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS
- Article number: ET0082
 CAS Number:
- 60-29-7
- EC number: 200-467-2
- Index number: 603-022-00-4
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the preparation: Laboratory reagent

· 1.3 Details of the supplier of the safety data sheet

1.3 Details of the supplier of the safety data shows the supplier of the safety data shows the supplier.
Scharlab, S.L.
C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN
Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65 email: scharlab@scharlab.com
Internet Web Site: www.scharlab.com

Regional representation: Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65 email: scharlab@scharlab.com Internet Web Site: www.scharlab.com

 Further information obtainable from: technical department
 1.4 Emergency telephone number: Please contact the regional Scharlab distributor/dealer in your country During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 1 H224 Extremely flammable liquid and vapour.

$\langle ! \rangle$

Acute Tox. 4 H302 Harmful if swallowed. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 21.12.2022

Scharlau

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 1)

Hazard pictograms



· Signal word Danger

- Hazard statements
- H224 Extremely flammable liquid and vapour.
- H302 Harmful if swallowed.
- H336 May cause drowsiness or dizziness.
- Precautionary statements
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P370+P378 P405 P501

In case of fire: Use CO2, powder or water spray to extinguish.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Substances
- CAS No. Description 60-29-7 diethyl ether
- · Identification number(s)
- *EC number:* 200-467-2
- · Index number: 603-022-00-4

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
 - In case of unconsciousness place patient stably in side position for transportation. *After skin contact:*

Generally the product does not irritate the skin.

- Immediately remove contaminated clothing.
- Immediately wash with water and soap and rinse thoroughly.

Printing date 21.12.2022

Scharlau

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. Call a doctor immediately.

- · After swallowing: Call for a doctor immediately.
- **4.2** Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.
- **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Highly flammable liquid and vapor.
- 5.3 Advice for firefighters
- **Protective equipment:** Wear fully protective suit.

Wear self-contained respiratory protective device.

Cool exposed containers with water spray or mist.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Eliminate all sources of ignition. Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Do not eat, drink or smoke during use. Wash hands after any manipulation. Open and handle receptacle with care.
- Information about fire and explosion protection:
 Use explosion-proof apparatus / fittings and spark-proof tools.
 Keep ignition sources away Do not smoke.

(Contd. on page 4)

Printing date 21.12.2022 Vers

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 3)

wise

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Scharlau

- *Requirements to be met by storerooms and receptacles:* Store in a cool, dry, well-ventilated place. Store only in unopened original receptacles. Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.
- Do not seal receptacle gas tight.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- See product's label for recommended storage temperature.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

60-29-7 diethyl ether

WEL Short-term value: 620 mg/m³, 200 ppm Long-term value: 310 mg/m³, 100 ppm

DNELs

DNEL worker, acute. Systematic effects: Inhalative - 616 mg/m3 DNEL worker, cronic. Systematic effects: Dermic - 44 mg/kg body weight DNEL worker, cronic. Systematic effects: Inhalative - 308 mg/m3 DNEL consumer, prolonged. Systematic effects:

- Inhalative: 54.5 mg/m3
- Dermic: 15.6 mg/kg body weight
- Oral: 15.6 mg/kg body weight
- · PNECs
- PNEC (Fresh water): 2 mg/L
- PNEC (Sea water): 0.2 mg/L
- PNEC (Freshwater sediments): 9.14 mg/kg
- PNEC (Seawater sediments): 0.914 mg/kg
- PNEC (Soil): 0.66 mg/kg
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- *Respiratory protection:* Not required.
- · Hand protection
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Printing date 21.12.2022

Scharlau

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 4)

- Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state
- · Colour:
- · Odour:
- Odour threshold:
- Melting point/freezing point:
 Boiling point or initial boiling point and
 boiling point or initial boiling point and
- boiling range · Flammability
- · Lower and upper explosion limit
- · Lower:
- · Upper:
- · Flash point:
- · Ignition temperature:
- · Decomposition temperature:
- · pH
- Viscosity:
- · Kinematic viscosity
- · Dynamic at 20 °C:
- · Solubility
- · water at 20 °C:
- Partition coefficient n-octanol/water (log value)
- Vapour pressure at 20 °C:
- · Density and/or relative density
- Density at 20 °C:
- · Relative density
- · Vapour density
- 9.2 Other information
- · Appearance:
- · Form:
- · Important information on protection of health and environment, and on safety.
- · Auto-ignition temperature:
- · Explosive properties:
- Molecular weight

Fluid Colourless Sweetish Not determined. -116.3 °C

35 °C Not applicable.

1.7 Vol % 48 Vol % -40 °C 170 °C Not determined. Not determined.

Not determined. 0.235 mPas

64.9 g/l

0.0211893 587 hPa

0.71 g/cm³ Not determined. Not determined.

Fluid

Not determined. May form explosive peroxides. 74.12 g/mol

(Contd. on page 6)

Printing date 21.12.2022 Version number 11.0 (replaces version 10.0) Revision: 02.12.2022 Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS (Contd. of page 5) · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void Flammable liquids Extremely flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void Pvrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void · Organic peroxides Void Corrosive to metals Void Desensitised explosives Void **SECTION 10: Stability and reactivity** · 10.1 Reactivity

Highly flammable liquid and vapor. Vapours may produce an explosive mixture with the air.

10.2 Chemical stability

Scharlau

- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions
 Danger of forming explosive hydrogen-air mixture when stored in enclosed spaces.

 Possible formation of peroxide.

wise

- 10.4 Conditions to avoid
 Heat, open flames and sparks
 Exposure to light
 Radiation
 Exposure to air.
 Dust generation and accumulation.
- 10.5 Incompatible materials:

ne wise choic

- Strong acids
- Strong oxidizing agents.
- 02
- H2O2 Air
- **10.6 Hazardous decomposition products:** Hydrogen
- Methane
- Carbon monoxide

(Contd. on page 7)

Printing date 21.12.2022

Scharlau

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 6)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if swallowed.
- LD/LC50 values relevant for classification:

Oral LD50 1,215 mg/kg (rat)

Inhalative LC50/4 h >20 mg/l (rat)

- Skin corrosion/irritation Skin - Rabbit Result: No irritation. May cause dermatitis.
- Serious eye damage/irritation Eyes - Rabbit
- Result: No eye irritation • **Respiratory or skin sensitisation** Sensibilizing test - Mouse Result: negative
- Human experience Result: negative
- Germ cell mutagenicity
- DNA inhibition

Mutagenicity (mammal cell test): chromosome aberration.

- Human lymphocytes
- Result: negative
- Mouse Lymphoma cells
- Result: negative
- Ames test

Salmonella typhimurium Result: negative

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by (IARC) International Agency of Research of Carcinogens.

· STOT-single exposure

Acute oral toxicity - Stomach/intestial disorders, risk of aspiration upon vomiting, pulmonary failure possible after aspiration of vomit.

- May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties Substance is not listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:
- Toxicity to fish
- LC50 static test Leuciscus idus (Golden orfe) 2840 mg/L 48 h Toxicity to daphnia and other aquatic invertebrates
- EC50 static test Ceriodaphnia (Water flea) 1380 mg/L 48 h
- Toxicity to algae
- ErC50 static test Desmodesmus subspicatus (green algae) 100 mg/L 72 h Toxicity to bacteria
- EC50 static test Activated sludge 21000 mg/L 3 min
- NOEC static test Activated sludge 42 mg/L 3 h

(Contd. on page 8)

Printing date 21.12.2022 Version number 11.0 (replaces version 10.0) Revision: 02.12.2022 Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS (Contd. of page 7) · 12.2 Persistence and degradability Easily biodegradable · 12.3 Bioaccumulative potential Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected. $\log Pow \le 4$ · 12.4 Mobility in soil No further relevant information available. · 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. vPvB: Not applicable. 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties. 12.7 Other adverse effects Additional ecological information: General notes: Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. SECTION 13: Disposal considerations 13.1 Waste treatment methods Recommendation Must be specially treated adhering to official regulations. Must not be disposed together with household garbage. Do not allow product to reach sewage system. · Uncleaned packaging: Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Packagings that may not be cleansed are to be disposed of in the same manner as the product. **SECTION 14: Transport information** 14.1 UN number or ID number ADR, IMDG, IATA UN1155 14.2 UN proper shipping name 1155 DIETHYL ETHER (ETHYL ETHER) · ADR · IMDG, IATA DIETHYL ETHER (ETHYL ETHER) 14.3 Transport hazard class(es) ADR, IMDG, IATA Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA 14.5 Environmental hazards:

- 14.5 Environmental
- Marine pollutant:

Scharlau

- 14.6 Special precautions for user
- Hazard identification number (Kemler code): 33

Warning: Flammable liquids.

No

(Contd. on page 9)


Printing date 21.12.2022

Scharlau

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS



SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I -
- Seveso category P5a FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- Contact: msds@scharlab.com

wise choic

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 1: Flammable liquids - Category 1 Acute Tox. 4: Acute toxicity - Category 4 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

(Contd. on page 10)

Printing date 21.12.2022

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 9)

Annex: Exposure scenario 1

· 1 - Short title of the exposure scenario Industrial use

Sector of Use

- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU8 Manufacture of bulk, large scale chemicals (including petroleum products)
- SU9 Manufacture of fine chemicals

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4 Chemical production where opportunity for exposure arises

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15 Use as laboratory reagent

Environmental release category

ERC1 Manufacture of the substance

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) Description of the activities / processes covered in the Exposure Scenario

- See section 1 of the annex to the Safety Data Sheet.
- · 2 Conditions of use
- · Duration and frequency Emission days (days/year): 300 8hrs (full working shift).
- · Physical parameters
- · Physical state Fluid
- Concentration of the substance in the mixture Raw material.

It covers a percentage of substance in the product up to 100 %

- Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

- Keep away from sources of ignition No smoking.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- Organisational protective measures

Handle the substance within a closed system.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour)

Ensure that the working area is organised, well lit and ventilated, with enough space to handle spilled product.

- Technical protective measures Provide explosion-proof electrical equipment. Ensure that suitable extractors are available on processing machines Only handle and refill product in closed systems. Store in cool, dry place in tightly closed receptacles.
 - Use product only in enclosed systems.

Drain the system before performing running operations or maintenance of equipment.

(Contd. on page 11)

Scharlau

regulation (EU) 2020/878 Printing date 21.12.2022 Version number 11.0 (replaces version 10.0) Revision: 02.12.2022 Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS (Contd. of page 10) · Personal protective measures Do not inhale gases / fumes / aerosols. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Measures for consumer protection Ensure adequate labelling. Environmental protection measures Water In case of discharge to a domestic wastewater treatment plant, it is not necessary to treat the wastewater in situ. Avoid spilling the substance without dissolving residual water in situ or recovering it from it. · Soil No significant emissions to the terrestrial environment are expected. Disposal measures Disposal must be made according to official regulations. Ensure that waste is collected and contained. Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system. · Waste type Partially emptied and uncleaned packaging 3 - Exposure estimation To estimate exposures in the workplace has been used ECETOC TRA tool unless otherwise indicated. Worker (dermal) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra PROC1: 0.34 mg/kg/day, RCR 0.01 PROC1: 1.37 mg/kg/day, RCR 0.03 PROC2: 1.37 mg/kg/day, RCR 0.03 PROC3: 0.34 mg/kg/day, RCR 0.01 PROC4: 6.86 mg/kg/day, RCR 0.16 PROC8a: 13.71 mg/kg/day, RCR 0.31 PROC8b: 6.86 mg/kg/day, RCR 0.16 PROC8b: 0.69 mg/kg/day, RCR 0.02 PROC15: 0.34 mg/kg/day, RCR 0.01 Worker (inhalation) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra. PROC1: 0.01 ppm, RCR 0.00 PROC1: 10 ppm, RCR 0.10 PROC2: 50 ppm, RCR 0.49 wise PROC2: 10 ppm, RCR 0.10 PROC3: 100 ppm, RCR 0.98 PROC4: 30 ppm, RCR 0.30 PROC8a: 50 ppm, RCR 0.49 PROC8b: 45 ppm, RCR 0.44 PROC8b: 15 ppm, RCR 0.15 PROC15: 50 ppm, RCR 0.49 · Environment ERC1: Fresh water 0.0028 mg/L, RCR 0.001381 ECR1: Freshwater sediment 0.0126 mg/kg dwt, RCR 0.001383 ERC1: Sea water 0.0002 g/L, RCR 0.001194 ERC1: Sea sediment 0.0010 mg/kg dwt, RCR 0.001201 ERC1: Soil 0.0021 mg/kg dwt, RCR 0.003136 ERC4: Fresh water 0.0028 mg/L, RCR 0.001381

(Contd. on page 12)

Printing date 21.12.2022

Scharlau

The wise choice

the wise choice

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 11)

wise

ERC4: Freshwater sediment 0.0126 mg/kg dwt, RCR 0.001383

he wise choice

The wise choice

- ERC4: Sea water 0.0002 mg/L, RCR 0.001194
- ERC4: Sea sediment 0.0010 mg/kg dwt, RCR 0.001201
- ERC4: Soil 0.0021 mg/kg dwt, RCR 0.003136
- · Consumer The exposure estimation was carried out in accordance with ECETOC TRA.
- 4 Guidance for downstream users
- Environment and Health: Used the model ECETOC TRA. If other measures for risk management / operating conditions are adopted, then users should ensure that these risks are at least at equivalent levels.

the wise choi

he wise choice

(Contd. on page 13)

the wise choice

The wise choice

Scharlau Safety data sheet according to 1907/2006/EC, Article 31 Commission

regulation (EU) 2020/878

Printing date 21.12.2022

Version number 11.0 (replaces version 10.0)

Revision: 02.12.2022

Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS

(Contd. of page 12)

Annex: Exposure scenario 2

· 1 - Short title of the exposure scenario Laboratory use Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites · Process category PROC10 Roller application or brushing PROC15 Use as laboratory reagent · Environmental release category ERC2 Formulation into mixture ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) · Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet. · 2 - Conditions of use Duration and frequency Emission days (days/year): 20 8hrs (full working shift). · Physical parameters Physical state Fluid Concentration of the substance in the mixture Raw material. It covers a percentage of substance in the product up to 100 % Other operational conditions · Other operational conditions affecting environmental exposure No special measures required. Other operational conditions affecting worker exposure Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking. Other operational conditions affecting consumer exposure during the use of the product Not applicable. **Risk management measures** Worker protection Organisational protective measures Provide a good standard of controlled ventilation (10 to 15 air changes per hour) Ensure that the working area is organised, well lit and ventilated, with enough space to handle spilled product. Ensure that activities are executed by specialists or authorised personnel only. Technical protective measures Provide explosion-proof electrical equipment. Ensure that suitable extractors are available on processing machines Personal protective measures Wear suitable gloves (tested to EN374) Measures for consumer protection Ensure adequate labelling. Environmental protection measures Air Volatile components subject to emission controls in the atmosphere. Water In case of discharge to a domestic wastewater treatment plant, it is not necessary to treat the wastewater in situ. Avoid spilling the substance without dissolving residual water in situ or recovering it from it. · Soil No significant emissions to the terrestrial environment are expected. · Disposal measures Disposal must be made according to official regulations. Ensure that waste is collected and contained. **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 14)

Scharlau

wise choice

re wise choi

Printing date 21.12.2022 Version number 11.0 (replaces version 10.0) Revision: 02.12.2022 Trade name: Diethyl ether, stabilized with approx. 7 ppm of 2,6-Di-tert-butyl-4-methylphenol (BHT), Multisolvent®, ACS (Contd. of page 13) · Waste type Partially emptied and uncleaned packaging · 3 - Exposure estimation To estimate exposures in the workplace has been used ECETOC TRA tool unless otherwise indicated. · Worker (dermal) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra. PROC10: 5.49 mg/kg/day, RCR 0.12 PROC15: 0.34 mg/kg/day, RCR 0.01 · Worker (inhalation) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra. PROC10: 75 ppm, RCR 0.74 PROC15: 50 ppm, RCR 0.49 Environment ERC2: Fresh water 0.604 mg/L, RCR 0.030202 ECR2: Freshwater sediment 0.2765 mg/kg dwt, RCR 0.30250 ERC2: Sea water 0.0060 g/L, RCR 0.030015 ERC2: Sea sediment 0.0275 mg/kg dwt, RCR 0.030195 ERC2: Soil 0.0042 mg/kg dwt, RCR 0.006297 ERC4: Fresh water 0.0604 mg/L, RCR 0.030202 ERC4: Freshwater sediment 0.2765 mg/kg dwt, RCR 0.030250 ERC4: Sea water 0.0060 mg/L, RCR 0.030015 ERC4: Sea sediment 0.0275 mg/kg dwt, RCR 0.030195 ERC4: Soil 0.0042 mg/kg dwt, RCR 0.006297 Consumer The exposure estimation was carried out in accordance with ECETOC TRA. 4 - Guidance for downstream users Environment and Health: Used the model ECETOC TRA. If other measures for risk management / operating conditions are adopted, then users should ensure that these risks are at least at equivalent levels. Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

wise

hewisecho