

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

Article number: HE0233

CAS Number:
110-54-3

EC number:
203-777-6

Index number:
601-037-00-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the preparation:

Organic solvent

Laboratory reagent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa

08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com

Internet Web Site: www.scharlab.com

Regional representation:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa

08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com

Internet Web Site: www.scharlab.com

Further information obtainable from: technical department

1.4 Emergency telephone number:

Please contact the regional Scharlab distributor/dealer in your country

During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



health hazard

Repr. 2

H361f Suspected of damaging fertility (causing atrophy of the testes).

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 1)



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02



GHS07



GHS08



GHS09

Signal word Danger**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361f Suspected of damaging fertility (causing atrophy of the testes).

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.1 Substances****CAS No. Description**

110-54-3 n-hexane

Identification number(s)**EC number:** 203-777-6

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 2)

• **Index number:** 601-037-00-0**SECTION 4: First aid measures**• **4.1 Description of first aid measures**• **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:**

Take affected persons into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

Use a respiratory bag or breathing device.

Do not use mouth to mouth or mouth to nose resuscitation.

Seek medical treatment.

• **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately remove contaminated clothing.

Wash contaminated clothing before reuse.

• **After eye contact:**

Rinse opened eye for several minutes under running water.

Eye contact causes painful burns that can cause permanent visual impairment or blindness.

Seek medical treatment.

• **After swallowing:**

Never give anything by mouth to an unconscious person.

Rinse mouth and drink water (2 glasses) if the affected is conscious. Seek medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting. Risk of perforation.

Call a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed**

The main symptoms are described for different cases of contact: Skin, eyes, inhalation and ingestion.

• **4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

SECTION 5: Firefighting measures• **5.1 Extinguishing media**• **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• **For safety reasons unsuitable extinguishing agents:** Water with full jet• **5.2 Special hazards arising from the substance or mixture** Highly flammable liquid and vapor.• **5.3 Advice for firefighters**• **Protective equipment:**

In the work of extinction it is necessary to provide respiratory protection and full chemical protective clothing.

Wear self-contained respiratory protective device.

Wear fully protective suit.

Stay in danger area only with artificial systems and independent breathing apparatus.

• **Additional information**

In the event of a major fire and large quantities, evacuate the area and fight the fire from a distance given the risk of explosion.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

Cool endangered receptacles with water spray.

(Contd. of page 3)

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Evacuate and restrict access.

Eliminate all sources of ignition.

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective clothing.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Do not eat, drink or smoke during use.

Wash hands after any manipulation.

Keep away from heat and sources of ignition.

Avoid breathing mist/vapours/spray.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool, dry, well-ventilated place.

Store only in unopened original receptacles.

Store in a cool location.

Information about storage in one common storage facility: Store away from foodstuffs.**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

See product's label for recommended storage temperature.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:** Not required.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 4)

• DNELs

DNEL for workers, cronic. Systematic effects:

- Inhalative: 3.25 mg/m³
- Dermic: 25.9 mg/kg body weight

• **Additional information:** The lists valid during the making were used as basis.

• 8.2 Exposure controls

• **Appropriate engineering controls** No further data; see item 7.

• **Individual protection measures, such as personal protective equipment**

• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties**• General Information****• Physical state**

Fluid

• Colour:

Colourless

• Odour:

Petrol-like

• Odour threshold:

Not determined.

• Melting point/freezing point:

-95 °C

• Boiling point or initial boiling point and boiling range

69 °C

• Flammability

Highly flammable.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 5)

• Lower and upper explosion limit	
• Lower:	1.2 Vol %
• Upper:	8.3 Vol %
• Flash point:	-22 °C
• Ignition temperature:	240 °C
• Decomposition temperature:	Not determined.
• pH	Not determined.
• Viscosity:	
• Kinematic viscosity	Not determined.
• Dynamic:	Not determined.
• Solubility	
• water at 20 °C:	0.06 g/l
• Partition coefficient n-octanol/water (log value)	0.34242-0.716
• Vapour pressure at 25 °C:	190 hPa
• Density and/or relative density	
• Density at 20 °C:	0.67 g/cm ³
• Relative density	Not determined.
• Vapour density	Not determined.
• 9.2 Other information	
• Appearance:	
• Form:	Fluid
• Important information on protection of health and environment, and on safety.	
• Auto-ignition temperature:	Not determined.
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
• Molecular weight	85.2 g/mol
• Change in condition	
• Evaporation rate	Not determined.
• Information with regard to physical hazard classes	
• Explosives	Void
• Flammable gases	Void
• Aerosols	Void
• Oxidising gases	Void
• Gases under pressure	Void
• Flammable liquids	Highly flammable liquid and vapour.
• Flammable solids	Void
• Self-reactive substances and mixtures	Void
• Pyrophoric liquids	Void
• Pyrophoric solids	Void
• Self-heating substances and mixtures	Void
• Substances and mixtures, which emit flammable gases in contact with water	Void
• Oxidising liquids	Void
• Oxidising solids	Void
• Organic peroxides	Void
• Corrosive to metals	Void
• Desensitised explosives	Void

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 6)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable at room temperature.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid**
Heat, open flames and sparks
Electrostatic charges
- **10.5 Incompatible materials:** Oxidising agents.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

Oral	LD50	16,750 mg/kg (rat)
Dermal	LD50	3,350 mg/kg (rabbit)
Inhalative	LC50/4 h	259,350 mg/l (rat)
- **Skin corrosion/irritation** Causes skin irritation.
- **Reproductive toxicity** Suspected of damaging fertility (causing atrophy of the testes).
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties** Substance is not listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
Toxicity to fish
CL50 - *Oryzias latipes* (Carp) - 13.37 mg/L (96h)
NOEC - *Oryzias latipes* (Carpa) - 2.99 mg/L (28h)
- **12.2 Persistence and degradability**
Biodegradability
Result: 98 % (Exposure time: 28 days) - OECD 301F
Easily biodegradable
- **12.3 Bioaccumulative potential**
Log Pow: 2.2 - 5.2 (25°C)
Bioconcentration factor (BCF): 10 - 2500
May be accumulated in organism
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 7)

• **12.7 Other adverse effects**

• **Remark:** Toxic for fish

• **Additional ecological information:**

• **General notes:**

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

• **13.1 Waste treatment methods**

• **Recommendation**

Must be specially treated adhering to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• **Uncleaned packaging:**

• **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

• **14.1 UN number or ID number**

• **ADR, IMDG, IATA**

UN1208

• **14.2 UN proper shipping name**

• **ADR**

1208 HEXANES, ENVIRONMENTALLY HAZARDOUS

• **IMDG**

HEXANES, MARINE POLLUTANT

• **IATA**

HEXANES

• **14.3 Transport hazard class(es)**

• **ADR, IMDG**



• **Class**

3 Flammable liquids.

• **Label**

3

• **IATA**



• **Class**

3 Flammable liquids.

• **Label**

3

• **14.4 Packing group**

• **ADR, IMDG, IATA**

II

• **14.5 Environmental hazards:**

Environmentally hazardous substance, liquid;
Marine Pollutant

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31 Commission regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 8)

- **Marine pollutant:** Yes (P)
Symbol (fish and tree)
 - **Special marking (ADR):** Symbol (fish and tree)
 - **14.6 Special precautions for user** Warning: Flammable liquids.
 - **Hazard identification number (Kemler code):** 33
 - **EMS Number:** F-E,S-D
 - **Stowage Category** E
 - **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
 - **Transport/Additional information:**
-
- **ADR**
 - **Limited quantities (LQ)** 1L
 - **Transport category** 2
 - **Tunnel restriction code** D/E
 - **UN "Model Regulation":** UN 1208 HEXANES, 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I -**
- **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** product safety department
- **Contact:** msds@scharlab.com
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
P: Marine Pollutant
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 10)

Annex: Exposure scenario 1

- **1 - Short title of the exposure scenario** Industrial use
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Process category** PROC15 Use as laboratory reagent
- **Environmental release category**
ERC2 Formulation into mixture
ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **2 - Conditions of use**
- **Duration and frequency**
8hrs (full working shift).
5 workdays/week.
Emission days (days/year): 20
- **Environment**
Estimated substance removal from wastewater via domestic sewage treatment (%): 96
Maximum allowable site tonnage based on release following total wastewater treatment removal (kg/day): 2400
Wastewater is to be treated by a municipal STP. Municipal STP discharge rate <2E3 m³/d.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity**
2 tons per year
100 kg per day
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure**
Fraction released to air from process (initial release previous to MGR): 0.025
Fraction released to residual water from process (initial release previous to MGR): 0.02
Fraction released to ground from process (initial release previous to MGR): 0.0001
Use only on hard ground.
- **Other operational conditions affecting worker exposure**
Avoid contact with the skin.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
Assumes use at not more than 20 °C above ambient temperature, unless stated differently.
Do not taste or swallow.
Do not ingest.
Do not induce vomiting
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
It is recommended to follow the current ATEX directive to explosive atmospheres
Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
Handle in a fume cupboard or under extract ventilation
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
Use product only in enclosed systems.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 11)

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Restrict line velocity during pumping to avoid generation of electrostatic discharge.

• **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Change contaminated clothing immediately.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Wear suitable protective gloves and protective goggles /face protection during work.

• **Measures for consumer protection** Ensure adequate labelling.

• **Environmental protection measures**

• **Air** No special measures required.

• **Water**

Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

Do not allow to reach sewage system.

• **Soil** Prevent contamination of soil.

• **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

• **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• **Waste type** Partially emptied and uncleaned packaging

• **3 - Exposure estimation**

• **Worker (oral)**

The exposure estimation was carried out in accordance with ECETOC TRA.

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at <http://www.ecetoc.org/tra>.

• **Worker (dermal)**

The exposure estimation was carried out in accordance with ECETOC TRA.

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at <http://www.ecetoc.org/tra>.

• **Worker (inhalation)**

The exposure estimation was carried out in accordance with ECETOC TRA.

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at <http://www.ecetoc.org/tra>.

• **Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

• **4 - Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

For the risk assessment, the tools recommended by ECHA can be used.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 12)

Annex: Exposure scenario 2

- **1 - Short title of the exposure scenario** Laboratory use
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Process category** PROC15 Use as laboratory reagent
- **Environmental release category**
ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **2 - Conditions of use**
- **Duration and frequency**
8hrs (full working shift).
5 workdays/week.
Emission days (days/year): 365
- **Environment**
Estimated substance removal from wastewater via domestic sewage treatment (%): 96
Maximum allowable site tonnage based on release following total wastewater treatment removal (kg/day): 370
Wastewater is to be treated by a municipal STP. Municipal STP discharge rate <2E3 m³/d.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity**
0.0028 tons per year
0.0075 kg per day
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure**
Fraction released to air from process (initial release previous to MGR): 0.5
Fraction released to residual water from process (initial release previous to MGR): 0.5
Fraction released to ground from process (initial release previous to MGR): 0
Use only on hard ground.
- **Other operational conditions affecting worker exposure**
Avoid contact with the skin.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
Assumes use at not more than 20 °C above ambient temperature, unless stated differently.
Do not taste or swallow.
Do not ingest.
Do not induce vomiting
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
It is recommended to follow the current ATEX directive to explosive atmospheres
Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
Handle in a fume cupboard or under extract ventilation
Provide a good standard of controlled ventilation (10 to 15 air changes per hour)
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
Use product only in enclosed systems.

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31 Commission
regulation (EU) 2020/878

Printing date 07.03.2023

Version number 6.0 (replaces version 5.0)

Revision: 07.03.2023

Trade name: n-Hexane, 96%, anhydrous (max. 0,002% H₂O)

(Contd. of page 13)

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Restrict line velocity during pumping to avoid generation of electrostatic discharge.

• **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Change contaminated clothing immediately.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Wear suitable protective gloves and protective goggles /face protection during work.

• **Measures for consumer protection** Ensure adequate labelling.

• **Environmental protection measures**

• **Air** No special measures required.

• **Water**

Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

Do not allow to reach sewage system.

• **Soil** Prevent contamination of soil.

• **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

• **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• **Waste type** Partially emptied and uncleaned packaging

• **3 - Exposure estimation**

• **Worker (oral)**

The exposure estimation was carried out in accordance with ECETOC TRA.

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at <http://www.ecetoc.org/tra>.

• **Worker (dermal)**

The exposure estimation was carried out in accordance with ECETOC TRA.

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at <http://www.ecetoc.org/tra>.

• **Worker (inhalation)**

The exposure estimation was carried out in accordance with ECETOC TRA.

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at <http://www.ecetoc.org/tra>.

• **Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

• **4 - Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

For the risk assessment, the tools recommended by ECHA can be used.