

Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Methanol, for GC residue analysis

· Article number: ME0318

· CAS Number:

67-56-1

· EC number:

200-659-6

· Index number:

603-001-00-X

- · Registration number 01-2119433307-44-XXXX
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation:

Laboratory reagent

Solvents

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com

Internet Web Site: www.scharlab.com

· Regional representation:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com Internet Web Site: www.scharlab.com

- · Further information obtainable from: technical department
- · 1.4 Emergency telephone number:

Please contact the regional Scharlab distributor/dealer in your country During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS06 skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.


(Contd. on page 2)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 1)



STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS06 GHS08

- Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapour.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H370 Causes damage to the central nervous system and the visual organs.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin.

with water [or shower].

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Additional information: Reserved for exclusive use in industrial facilities
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description

67-56-1 methanol

- · Identification number(s)
- **EC number:** 200-659-6
- Index number: 603-001-00-X

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Remove breathing equipment only after contaminated clothing have been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Take affected persons into fresh air and keep quiet.

(Contd. on page 3)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 2)

Supply fresh air and to be sure call for a doctor.

In severe cases such as cardiorespiratory arrest, artificial respiration techniques such as mouth-to-mouth resuscitation, cardiac massage, oxygen supply, etc. will be applied.

· After skin contact:

Immediately remove contaminated clothing.

Immediately wash with water and soap and rinse thoroughly.

Call a doctor immediately.

If the product causes burns or frostbite, clothing should not be removed because it could worsen the injury if it sticks to the skin.

In the event of blisters forming on the skin, these should never be burst as this would increase the risk of infection.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Prevent the affected person from rubbing or closing their eyes.

In the event that the injured person wears contact lenses, they must be removed as long as they are not stuck to the eyes, otherwise additional damage could occur.

· After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately

Induce vomiting only, if affected person is fully conscious.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

ABC powder

Foam

Carbon dioxide

Do NOT use pressurized water.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

In the work of extinction it is necessary to provide respiratory protection and full chemical protective clothing.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Isolate leaks as long as it does not pose an additional risk to the people who perform this function. Avoid sources of ignition.

Ventilate area.

Use water fog to evaporate or ventilate.

If confined space, use self-contained breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep receptacles tightly sealed.

Keep away from heat and sources of ignition.

Do not eat, drink or smoke during use.

Wash hands after any manipulation.

Only handle and refill product in closed systems.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Handle only outside or in explosion protected rooms.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Avoid sources of heat, radiation, static electricity and contact with food.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Sk

· DNELs

DNEL worker, cronic. Systematic effects: Dermic - 40 mg/kg body weight

DNEL worker, cronic. Acute local and systematic effects: Inhalative - 260 mg/m3

DNEL consumer, prolonged. Systematic effects: Oral - 8 mg/kg body weight

DNEL consumer, prolonged. Systematic effects: Dermic - 8 mg/kg body weight

DNEL consumer, prolonged. Local effects: Inhalative - 50 mg/m3

DNEL consumer, prolonged. Systematic effects: Inhalative - 50 mg/m3

· PNECs

PNEC (Fresh water): 154 mg/L PNEC (Sea water): 15.4 mg/L

PNEC (Freshwater sediments): 570.4 mg/kg

PNEC (Soil): 23.5 mg/kg

PNEC (Residual water depuration system): 100 mg/kg

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 4)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Face protection

Body protection:

Protective clothing against chemical risks, antistatic and flame retardant.

Boots

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- Appearance:

Form: Fluid Colourless

Odour: Alcohol-like

Odour threshold: Not determined.

· pH-value:

· Change in condition

Melting point/freezing point: -98 °C Initial boiling point and boiling range: 64.7 °C

· Flash point: 10 °C

(Contd. on page 6)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 5)

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 455 °C

Decomposition temperature: Not determined.
 Auto-ignition temperature: Not determined.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 7.3 g/m³ 36 g/m³ Upper: Vapour pressure at 20 °C: 169 hPa 0.792 g/cm3 · Density at 20 °C: 792 kg/m3 · Bulk density: Not determined. Relative density Vapour density Not determined. Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Fully miscible.Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid

Heat

Exposure to light

· 10.5 Incompatible materials:

Acids ans bases Oxidising materials.

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

Oral LD50 100 mg/kg (rat)
Dermal LD50 300 mg/kg (rabbit)
Inhalative LC50/4 h 3 mg/l (rat)

(Contd. on page 7)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 6)

- · Primary irritant effect:
- · Skin corrosion/irritation It can be fatal if the product is absorbed through the skin.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

Ingestion, inhalation or skin absorption of this product poses a danger of serious irreversible effects caused by a single exposure.

- Causes damage to the central nervous system and the visual organs.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CL50 (pez) - Leopomis macrochirus - 15400 mg/L (96h)

CE50 (algae) - Microcystis aeruginosa - 12000 mg/L (96h)

CE50 (daphnia) - Nitrocra spinipes - 530 mg/L (168h)

· 12.2 Persistence and degradability

Chemical Oxygen Demand (COD) - 1.42 mg/g

Remarks: (IUCLID) Easily biodegradable

· 12.3 Bioaccumulative potential

Bioconcentration factor (BCF): 3

log Pow ≤ -0.77

- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

(Contd. on page 8)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

· 14.2 UN proper shipping name

· ADR · IMDG, IATA

· 14.3 Transport hazard class(es)

1230 METHANOL **METHANOL**

UN1230

· ADR





3 Flammable liquids. · Class · Label 3+6.1

· IMDG





 Class 3 Flammable liquids.

· Label 3/6.1

· IATA





3 Flammable liquids. · Class

· Label 3 (6.1)

. 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 336 · EMS Number: 3-06

· Stowage Category

· Stowage Code SW2 Clear of living quarters.

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 1L · Transport category 2 · Tunnel restriction code D/E

UN 1230 METHANOL, 3 (6.1), II · UN "Model Regulation":

(Contd. on page 9)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is listed.
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 500 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 5000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40, 69
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II Substance is not listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: product safety department
- Contact: msds@scharlab.com
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity - Category 3

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

(Contd. on page 10)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 9)

Annex: Exposure scenario 1

- · 1 Short title of the exposure scenario Industrial use
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Process category PROC15 Use as laboratory reagent
- · Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Description of the activities / processes covered in the Exposure Scenario
 See section 1 of the annex to the Safety Data Sheet.

- · 2 Conditions of use
- · Duration and frequency

4 hrs (half working shift).

Emission days (days/year): 240

- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Risk management measures

Use in a ventilated with filtered air pressurized cabin. Effectiveness 90%

- Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Detailed measures on hand protection according to Safety Data Sheet, section 8.

- · **Measures for consumer protection** Ensure adequate labelling.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Soil No special measures required.
- · Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

(Contd. on page 11)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 10)

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging

· 3 - Exposure estimation

To estimate exposures in the workplace has been used ECETOC TRA tool unless otherwise indicated.

· Worker (oral)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (dermal)

PROC 15: 0.34 (mg/kg/d)

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (inhalation)

PROC 15: 6.67 (mg/m3)

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

Environment

Detailed information on the estimation of the environmental exposure can be found at http://ecb.jrc.ec.europa.eu/euses/.

· 4 - Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

For the risk assessment, the tools recommended by ECHA can be used.

(Contd. on page 12)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 11)

Annex: Exposure scenario 2

- · 1 Short title of the exposure scenario Laboratory use
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Process category PROC15 Use as laboratory reagent
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

- Description of the activities / processes covered in the Exposure Scenario
 See section 1 of the annex to the Safety Data Sheet.
- · 2 Conditions of use
- · Duration and frequency

4 hrs (half working shift).

Emission days (days/year): 240

- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· Risk management measures

Use in a ventilated with filtered air pressurized cabin. Effectiveness 80%

- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Detailed measures on hand protection according to Safety Data Sheet, section 8.

- Measures for consumer protection Ensure adequate labelling.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- Soil No special measures required.
- · Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.
- · Disposal measures

Disposal must be made according to official regulations.

(Contd. on page 13)



Printing date 13.06.2022 Version number 13.0 Revision: 13.06.2022

Trade name: Methanol, for GC residue analysis

(Contd. of page 12)

Ensure that waste is collected and contained.

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging

· 3 - Exposure estimation

To estimate exposures in the workplace has been used ECETOC TRA tool unless otherwise indicated.

· Worker (oral)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (dermal)

PROC 15: 0.34 (mg/kg/d)

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (inhalation)

PROC 15: 6.67 (mg/m3)

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

Environment

Detailed information on the estimation of the environmental exposure can be found at http://ecb.jrc.ec.europa.eu/euses/.

· 4 - Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

For the risk assessment, the tools recommended by ECHA can be used.