

Identification

(NH₄)₂SO₄

M = 132,14 g/mol

CAS [7783-20-2]

EC number: 231-984-1

Taric code: 3102 21 00

Synonyms

Sulfuric acid diammonium salt

Applications

analytical chemistry, manufacture of alums.

Specifications

assay (acidimetric).....	min. 99,0 %	calcium (Ca).....	max. 0,001 %
identity (IR-spectrum).....	passes test	copper (Cu).....	max. 2 ppm
insoluble matter.....	max. 0,005 %	heavy metals.....	max. 5 ppm
pH (5 %, H ₂ O).....	5,0 - 6,0	iron (Fe).....	max. 2 ppm
chlorides (Cl).....	max. 3 ppm	lead (Pb).....	max. 2 ppm
nitrates (NO ₃).....	max. 0,001 %	magnesium (Mg).....	max. 5 ppm
phosphates (as PO ₄).....	max. 5 ppm	zinc (Zn).....	max. 1 ppm
arsenic (As).....	max. 0,2 ppm	residue on ignition.....	max. 0,005 %
cadmium (Cd).....	max. 1 ppm	loss on drying (105 °C).....	max. 0,1 %

Physical data

- Appearance: crystals, colourless
- Spec. Density: 1,77 g/cm³
- Bulk density: ~ 850 kg/m³
- Solub. in water: (20 °C): 754 g/l
- Melting point: 280 °C (decomposes)
- pH(50 g/l H₂O, 20 °C) ~ 5 - 6

Safety - GHS

Signal Word: Warning



Hazard Statements:

- H315: Causes skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.

Precautionary Statements:

- P261: Avoid breathing dust / fume / gas / mist / vapours / spray.
P280: Wear protective gloves / protective clothing / eye protection / face protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321: Specific treatment (see on this label).
P405: Store locked up.
P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

Transport/storage

- 10°C - 30°C