


Identification

C_5H_{12}
 M = 72,15 g/mol
 CAS [109-66-0]
 EC number: 203-692-4
 Taric code: 2901 10 00


Synonyms

1,3-Dimethylpropane, Diethyl methane

Applications

synthesis of organic products, analytical chemistry, reference material, chromatography.

Specifications

assay (G.C.).....	min. 99 %	copper (Cu).....	max. 0,02 ppm
identity (IR-spectrum).....	passes test	iron (Fe).....	max. 0,1 ppm
density (20°/4°).....	0,625 - 0,627	lead (Pb).....	max. 0,1 ppm
colour (Hazen).....	max. 10	magnesium (Mg).....	max. 0,1 ppm
acidity.....	max. 0,0002 meq/g	manganese (Mn).....	max. 0,02 ppm
aluminium (Al).....	max. 0,5 ppm	nickel (Ni).....	max. 0,02 ppm
barium (Ba).....	max. 0,1 ppm	tin (Sn).....	max. 0,1 ppm
boron (B).....	max. 0,02 ppm	zinc (Zn).....	max. 0,1 ppm
cadmium (Cd).....	max. 0,05 ppm	sulphur compounds (as S).....	max. 0,005 %
calcium (Ca).....	max. 0,5 ppm	substances darkened by H ₂ SO ₄	passes test
chromium (Cr).....	max. 0,02 ppm	residue on evaporation.....	max. 0,001 %
cobalt (Co).....	max. 0,02 ppm	water (K.F.).....	max. 0,01 %

Physical data

- Density: 0,63 g/cm³
- Solub. in water: (25 °C): 0,04 g/l
- Melting point: -129,7 °C
- Boiling point: 36,1 °C
- Flash point: -48 °C
- Ignition temperature: 285 °C
- Vapour pressure: (20 °C) 573 hPa
- Dielectric const.: (20 °C) 1,8
- Evap. heat: (36 °C) 383 KJ/kg
- Saturation conc.: (20 °C) 1689 g/m³
- Expl. limit (upper): 8 Vol%
- Expl. limit (lower): 1,4 Vol%

Safety - GHS

Signal Word: Danger

Hazard Statements:

- H225: Highly flammable liquid and vapour.
 H304: May be fatal if swallowed and enters airways.
 H336: May cause drowsiness or dizziness.
 H411: Toxic to aquatic life with long lasting effects.
 EUH066: Repeated exposure may cause skin dryness or cracking.


Precautionary Statements:

- P210: Keep away from heat / sparks / open flames / hot surfaces. - No smoking.
 P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
 P370+P378: In case of fire: Use ... for extinction.
 P405: Store locked up.
 P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

Transport/storage

- ADR: 3 F1 II • UN 1265 • PENTANES, liquid
- IMDG: 3 II • UN 1265 • PENTANES
- IATA/ICAO: 3 II • UN 1265 • PENTANES
- PAX: 305
- CAO: 307
- 15°C - 25°C