

Identification

KOH M = 56,11 g/mol CAS [1310-58-3] EC number: 215-181-3 Taric code: 2815 20 90

Applications

analytical chemistry, laboratory reagent, titrant in volumetric analysis.

Specifications

factor.....0,999 - 1,001 uncertainty ± 0,001

1 ml = 0,11222 g KOH

This solution was analysed using a certified reference material (potassium hydrogen phthalate). The certified reference material is ISO 17034 accredited, measured according to ISO/IEC 17025 and traceable to the International System of Units by means of a Standard Reference Material from NIST: SRM® 84 (Potassium Hydrogen Phthalate).

Physical data

• Density: ~ 1,09 g/cm3 • pH>10

Safety - GHS Signal Word:

Danger

Hazard Statements:

H314: Causes severe skin burns and eye damage.

Precautionary Statements:

P260: Do not breathe dust / fume / gas / mist / vapours / spray.

P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor / physician.

P405: Store locked up.

P501a: Dispose of contents / container in accordance with local / regional / national / international regulations.

Transport/storage

- ADR: 8 C5 II UN 1814 POTASSIUM HYDROXIDE SOLUTION
- IMDG: 8 II UN 1814 POTASSIUM HYDROXIDE SOLUTION
- IATA/ICAO: 8 II UN 1814 POTASSIUM HYDROXIDE SOLUTION
- PAX: 809
- CAO: 813
- 10°C 30°C

